# **RLF-6914**

### 6" SQUARF LFD ULTRA SLIM SLIM DOWNLIGHTS WITH WHITE TRIM



Fixture Type

Project

Notes







RLF-6914-SW5-WH complete set

This Ultra Slim Recessed Downlight series is perfect for tight spaces such as soffits, insulated, and suspended ceilings. With a very wide 120° beam angle, a very high color rendering index (CRI) of 90+, this fixture can easily be installed in virtually any application where space is at a premium. At just under an inch deep, and IC rated, it can fit even directly below ceiling joists (flush to ceiling). Plug-and-Play Remote Driver is included as well as a Matte White metal trim. Suitable for Indoor Wet Locations and Triac dimming with 5-Level field-selectable Color Temperature. Optional decorative trim rings in Black and Brushed Nickel finishes available and optional universal New Construction mounting plate with hanger bars available.























#### **SPECIFICATIONS**

INPUT VOLTAGE	120V AC
WATTAGE	14 W
LUMENS	900 Lm
EFFICACY	64 Lm/W
CRI	90+
BEAM ANGLE	120°
DIMMING <sup>1</sup>	TRIAC Dimming
CUT-OUT	6-1/4" Ø

<sup>&</sup>lt;sup>1</sup> Effectively dim down to 10% / See other compatible dimmers on the next page


#### **RATINGS** IC, Airtight **ENVIRONMENT** Indoor - Wet **CERTIFICATIONS** cETLus, T24 Compliant **LUMEN MAINTENANCE** 50,000 hours **INCLUDES** Remote driver and matte white metal trim **OPTIONAL** Other trims colors and universal mounting plate WARRANTY<sup>2</sup> 5 years

#### **PERFORMANCE**

CCT selectable via switch on heatsink


COLOR TEMPERATURE <sup>3</sup>		LUMEN <sup>4</sup>	WATTAGE	EFFICACY	CRI
	SW5 (27/30/35/40/50K) <sup>5</sup>	900 Lm	14 W	64 Lm/W	90+

<sup>3 &</sup>amp; 4 CCT within +/-10%



#### ORDERING INFO

STEP 1 - Light Engine with LED, Driver and White Matte Metal Frame



#### STEP 2 - Optional Trim (Sold separately)





MODEL RLT-69 - Square Trim **FINISH** 

BK - Black

**BN** - Brushed Nickel

## **OPTIONAL ACCESSORY**

(Sold separately)



MODEL RLH-346-NC-UNI

Universal mounting plate with hanger bars. For cutout sizes: 3", 4-1/4" or 6-1/4"

15 Harbor Park Drive Port Washington, NY 11050 Fax

800 527 7796 855 265 5768



219 South 6th Ave City of Industry, CA 91746 Main 800 527 7796 855 265 5768



support@jescolighting.com Tech Support 855 592 0029

<sup>&</sup>lt;sup>2</sup> See published warranty terms for detailed information


<sup>&</sup>lt;sup>5</sup> Switchable CCT

# **RLF-6914**

6" SQUARE LED ULTRA SLIM SLIM DOWNLIGHTS WITH WHITE TRIM



#### **TECHNICAL DRAWING**





DIMENSIONS					
Α	6-7/8" 152 mn				
В	1"	24 mm			
С	3-3/8''	87 mm			
D	1-3/8''	35 mm			
Е	18''	457 mm			

#### **COMPATIBLE DIMMERS**

COOPER	SI06P
LEVITON	6621, 6672, IPL06-10Z
LUTRON	PD-6WCL, DVCL-153P, SFTU-5A3P, DMD-LE3-D, CTCL-153P, DV-600P



